

MATRIX GOLD LINK ROLL

Product Description

Name : MATRIX GOLD LINK ROLL

Type : Dry Sanding

Backing : Cwt-Kraft Paper

Bonding : Resin Over Resin

Grain : Aluminium Oxide

Coating : Open Coat

Shape : Disc 5" PSA (Link Roll)



Available Grit

| 40 | 09 | 08 | 100 | 120 | 150 | 180 | 220 | 240 | 780 | 320 | 360 | 400 | 200 | 009 | 800 | 1000 | 1200 | 1500 | 2000 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|
| | • | • | • | • | | • | | • | | • | | • | | | | | | | |

Polishing Method







Product Features

- Rapid workability for industry and automotive refinish
- Durable backing and grain
- Anti-clogging

- High quality surface finishing
 - O Coarser grit remove old paint film and putty
 - O Finer grit primer and lacquer

Applications

Workpieces

- Automotive
- Metal
- Wood
- Putty / Filler

Packaging Size

| | Package Size of Sheet | | | | | | |
|--------|--------------------------------|------------|--|--|--|--|--|
| Grit | (Matrix Gold Link Roll 5" PSA) | | | | | | |
| | Roll/Box | Box/Carton | | | | | |
| 60-400 | 1 | 12 | | | | | |

Remark: 100 Disc/Roll

Handling and Storage

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

Safety and Disposal

- For full Health and Safety information please refer to Material Safety Data Sheet
- Observe the precautionary notices displayed on the sleeve
- Goggles and suitable protective equipment must be worn while using these products
- Good ventilation must be provided in the working environment

