

D-CUT TOA

Product Description

Name : D-CUT
 Type : Dry Sanding
 Backing : Cwt Paper-Latex Paper
 Bonding : Resin over Resin
 Grain : Aluminium Oxide (Heat Treatment)
 Coating : Close Coat
 Shape : Sheet, Roll, Disc

Available Grit															
60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000
▪	▪	▪	▪	▪	▪	▪	▪	▪	▪	▪	▪	▪	▪	▪	▪

Product Features

- High performance cutting and sanding ability.
- Excellent grain support.
- Provide high stock removal.
- Excellent anti-clogging from sanding dust.
- Long lasting sanding ability.

Applications

Workpieces

- Wood and Furniture
- Wooden Paint
- Lacquer sanding sealer
- Plastic

Available Sander / Grinder

- Disc Sander
- Orbital Sander
- Hand Sander

Recommendations

- Select grit number of abrasive paper suitable to the sanding surface

Application	Grit No.
• Cutting down Wood surface	60-150
• Surface Condition	180-240
• Primer, Sealer	280-320
• Topcoat, Clear Laquer	360-600
• Finishing	800-1000

Packaging Size

Sheet

Grit no.	Sheet/ Sleeve	Sleeve/ Carton	Sheet/ Carton
60-180	100	5	500
220-1000	100	10	1000

Roll

Grit no.	Size	Roll/ Pack
60-1000	930MMx100M	1

Disc

Grit no.	Disc/Pack	Pack/ Carton	Disc/ Carton
60-1000	50	20	1000

Handling and Storage

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

Safety and Disposal

- For full Health and Safety information please refer to Material Safety Data Sheet
- Observe the precautionary notices displayed on the sleeve
- Goggles and suitable protective equipment must be worn while using these products
- Good ventilation must be provided in the working environment