

# LAC GOLD RFG SOFT FLEX

## **Product Description**

Name : LAC GOLD RFG SOFT FLEX

Type : Dry Sanding

Backing: #180-#2000 Bwt. Latex paper

Attachment : PU Sponge Bonding : Resin over Resin

Grain : Aluminium Oxide (Heat Treatment)

Coating : Open Coat

Shape : Sheet size 115 mm. x 125 mm.

	Available Grit																		
40	09	08	100	120	150	180	220	240	280	320	360	400	200	009	008	1000	1200	1500	2000
						-	-		-	•	-	-	-	-	-		•		•

## **Product Features**

- · Higher level of abrasive on a curved surface
- · Available for uniform abrasion without deep scratches
- · Durable backing and grain
- · Anti-Clogging
- · Perfect Finishing Surface

## **Applications**

#### Workpieces

- Automotive paint
- Primer
- Putty
- Top Coat and Lacquer
- Plastic

# Available Sander / Grinder

• Hand Sanding

## Recommendations

• Select grit number of abrasive paper suitable to the sanding surface

Application	Grit No.
Plastic, Putty	180-320
Primer Surface	320-1000
Topcoat, Clear surface, Finishing	1000-2000

# **Handling and Storage**

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

# Safety and Disposal

- $\bullet$  For full Health and Safety information please refer to Material Safety Data Sheet
- $\bullet$  Observe the precautionary notices displayed on the sleeve
- $\bullet$  Goggles and suitable protective equipment must be worn while using these products

First Issue Date: 09/02/2023

 $\bullet$  Good ventilation must be provided in the working environment