MATRIX BLEND-IN LEVELLER #1742

Product Description	Matrix Blen-In Leveller is feather-edge agent or blending levelling agnet between old paint film and new paint film to protect the polishing mark after polish by polishing compound and waxes.
Mixing Ratio	It doesn't mix with anythings and dilute with thinner. It can mix with paint for the last paint application.
Usage	- To use for spot repair. - To apply around damage area or spot repair which will apply paint. It will be applied to cover new paint film area and new paint's feather-edge is on it, too. - After apply the feather-edge agent or Matrix Blen-In Leveller, air dery it about 1 - 5 minutes bofore apply the next step paint. - For solid colors, mix the feather-edge agent with paint in ratio 1:1 to apply for the last application time to increase adhesion of topcoat clear and protect feather-edge mark between old paint film and new paint film - Matrix Blen-In Leveler has property to be adhesive promotion agent, too. So, we can apply to increase adhesion between old paint film and new paint film.
Spray gun	Gravity Feed
Nozzle size	1.3 - 1.4 mm. (Please refer to spray gun manufacturer)
Spray pressure	1.5 - 2.0 Bar
Number of spray coats	Apply 1 - 2 times
Handling and Storage	The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition.
Shelf life	48 months at <40 ^{0}C
Safety and Disposal	- Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately. - For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Safety Data Sheet.