# KURUMA RUBBING COMPOUND

V.1/26

## Product Description

An all-round Performance Cutting Compound is specially formulated to deliver outstanding scratch removal performance and a high gloss finish on new and old paint.

- Optimum scratch removal-can be used with most types of compounding pads, foam or lambswool, to enable the fast and efficient removal of paintwork defects, even from old or the hardest of lacquer finishes.
- Easy-to-use- reduces process time by removing scratches quicker, without damaging the lacquer surface and is easy to clean-up leaving a high clarity, deep gloss shine.
- Permanent Scratch Removal- employs an advanced abrasive system to quickly and permanently remove scratches, does not hide imperfections with cosmetic oil/fillers.
- For use-on all automotive paint systems including water based, HS high solid, MS, infrared and accelerator cured paints, single component and 2-pack, acrylic, cellulose, synthetic and OEM finishes.
- Bodyshop Approved- Silicone Free – Paintable!
- Low V.O.C. - Low V.O.C. product and Non-flammable.

## Direction to use

Cutting compound can be applied by hand (for small areas) or by machine for larger areas

By Machine :

Use machine speed of between 1200-2000 rpm (free running).

1. Apply Paste compound in small quantities to paint surfaces (use minimum amount to work required area).
2. Work the surface applying medium pressure until the scratches and imperfections are removed.
3. Reduce pressure as the mop starts to move freely to allow polishing action to take place.
4. After compounding remove any residue and buff surface with clean soft micro-fibre cloth.

By Hand :

Use 100% fine cotton cloth to avoid introducing any scratches to sensitive paint finishes. Apply to paint ☐ surface, and work around area. Do not allow to fully dry out. Remove residues with a clean, soft microfiber cloth and buff to shine. Repeat process until imperfections have been removed.☐

## Additional Information

Professional users may refer to the Safety Data Sheet for this product available upon request.

Shelf Life: 2 years shelf life when unopened and stored in a cool dry place

Storage and Handling: Store at room temperature. Protect from frost.