MATRIX POLY PUTTY

Product Description

Matrix Poly Putty is poly putty or air dry putty which is quick dry, very good sandability and non-sinking. It's suitable for thin application and easy to be smooth putty knife because it's fine particle. It doesn't stick with sandpaper and good featheredge. It's very strong internal adhesion sinking under right mixing ratio between base and hardener.

Substrate preparation

- Clean surface to be dry and without wax, grease, dust and foreign matters.
- Remove the old paint film with dry sandpaper no.80 , then make featheredge with sandpaper no. 120.

Mixing Ratio

- Two Component System

	Weight
Matrix Poly Putty Part A	100
Matrix Poly Putty Part B	2

Mix Part A and Part B, strictly follow mix ratio until the mixture is homogeneous before application.
After mixed, apply within 3-5 minutes

Drying Time

Dry to sand : 30 mins @ 30^{o}C

Sanding

- Dry sandpaper no. 120, 240
- Wet sandpaper no. 120, 240

Handling and Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Shelf life

- 6 months at <40^{o}C

Safety and Disposal

- Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.
- For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Safety Data Sheet.